

section does not require that the person on duty be at the control point or continuously monitor all transmissions of the station. However, the control point must have facilities that enable the person on duty to turn off the transmitters in the event of a malfunction.

TECHNICAL REQUIREMENTS

§ 22.351 Channel assignment policy.

The channels allocated for use in the Public Mobile Services are listed in the applicable subparts of this part. Channels and channel blocks are assigned in such a manner as to facilitate the rendition of service on an interference-free basis in each service area. Except as otherwise provided in this part, each channel or channel block is assigned exclusively to one common carrier in each service area. All applicants for, and licensees of, stations in the Public Mobile Services shall cooperate in the selection and use of channels in order to minimize interference and obtain the most efficient use of the allocated spectrum.

§ 22.352 Protection from interference.

Public Mobile Service stations operating in accordance with FCC rules that provide technical channel assignment criteria for the radio service and channels involved, all other applicable FCC rules, and the terms and conditions of their authorizations are normally considered to be non-interfering. If the FCC determines, however, that interference that significantly interrupts or degrades a radio service is being caused, it may, in accordance with the provisions of sections 303(f) and 316 of the Communications Act of 1934, as amended, (47 U.S.C. 303(f), 316), require modifications to any Public Mobile station as necessary to eliminate such interference.

(a) *Failure to operate as authorized.* Any licensee causing interference to the service of other stations by failing to operate its station in full accordance with its authorization and applicable FCC rules shall discontinue all transmissions, except those necessary for the immediate safety of life or property, until it can bring its station

into full compliance with the authorization and rules.

(b) *Intermodulation interference.* Licensees should attempt to resolve such interference by technical means.

(c) *Situations in which no protection is afforded.* Except as provided elsewhere in this part, no protection from interference is afforded in the following situations:

(1) *Interference to base receivers from base or fixed transmitters.* Licensees should attempt to resolve such interference by technical means or operating arrangements.

(2) *Interference to mobile receivers from mobile transmitters.* No protection is provided against mobile-to-mobile interference.

(3) *Interference to base receivers from mobile transmitters.* No protection is provided against mobile-to-base interference.

(4) *Interference to fixed stations.* Licensees should attempt to resolve such interference by technical means or operating arrangements.

(5) *Anomalous or infrequent propagation modes.* No protection is provided against interference caused by tropospheric and ionospheric propagation of signals.

(6) *Facilities for which the Commission is not notified.* No protection is provided against interference to the service of any additional or modified transmitter operating pursuant to §§ 1.929 or 22.165, unless and until the licensee modifies its authorization using FCC Form 601.

(7) *In-building radiation systems.* No protection is provided against interference to the service of in-building radiation systems (see § 22.383).

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11633, Mar. 12, 1997; 63 FR 68944, Dec. 14, 1998]

§ 22.353 Blanketing interference.

Licensees of Public Mobile Services stations are responsible for resolving cases of blanketing interference in accordance with the provisions of this section.

(a) Except as provided in paragraph (c) of this section, licensees must resolve any cases of blanketing interference in their area of responsibility

caused by operation of their transmitter(s) during a one-year period following commencement of service from new or modified transmitter(s). Interference must be resolved promptly at no cost to the complainant.

(b) The area of responsibility is that area in the immediate vicinity of the transmitting antenna of stations where the field strength of the electromagnetic radiation from such stations equals or exceeds 115 dBuV/m. To determine the radial distance to the boundary of this area, the following formula must be used:

$$d = 0.394 \times \sqrt{p}$$

where d is the radial distance to the boundary, in kilometers

p is the radial effective radiated power, in kilowatts

The maximum effective radiated power in the pertinent direction, without consideration of the antenna's vertical radiation pattern or height, must be used in the formula.

(c) Licensees are not required to resolve blanketing interference to mobile receivers or non-RF devices or blanketing interference occurring as a result of malfunctioning or mistuned receivers, improperly installed consumer antenna systems, or the use of high gain antennas or antenna booster amplifiers by consumers.

(d) Licensees that install transmitting antennas at a location where there are already one or more transmitting antennas are responsible for resolving any new cases of blanketing interference in accordance with this section.

(e) Two or more licensees that concurrently install transmitting antennas at the same location are jointly responsible for resolving blanketing interference cases, unless the FCC can readily determine which station is causing the interference, in which case the licensee of that station is held fully responsible.

(f) After the one year period of responsibility to resolve blanketing interference, licensees must provide upon request technical information to complainants on remedies for blanketing interference.

§ 22.355 Frequency tolerance.

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

TABLE C-1—FREQUENCY TOLERANCE FOR TRANSMITTERS IN THE PUBLIC MOBILE SERVICES

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

[61 FR 54099, Oct. 17, 1996]

§ 22.357 Emission types.

Any authorized station in the Public Mobile Services may transmit any emission type provided that the resulting emission complies with the appropriate emission mask. See §§ 22.359, 22.861 and 22.917.

[61 FR 54099, Oct. 17, 1996]

§ 22.359 Emission masks.

Unless otherwise indicated in the rules governing a specific radio service, all transmitters intended for use in the Public Mobile Services must be designed to comply with the emission masks outlined in this section. If an emission outside of the authorized bandwidth causes harmful interference, the FCC may, at its discretion, require greater attenuation than specified in this section.

(a) *Analog modulation.* For transmitters other than those employing digital modulation techniques, the mean or peak envelope power of adjacent channel emissions must be attenuated below the output mean or peak envelope power of the total emission (P, in Watts) in accordance with the following schedule:

(1) On any frequency removed from the center frequency of the assigned channel by more than 50 percent up to and including 100 percent of the authorized bandwidth:

at least 25 dB: